

Thermocenter.

TC40+/TC80+/TC160/TC240/TC400

The SalvisLab Thermocenter sets standards in quality and design. Short heating and precise temperature control make the Thermocenter an ideal solution for heating and drying tasks of any kind. With the fans and heating elements in the rear part of the housing the Thermocenter guarantees reliability and precision down to the last corner. The clearly arranged touch screen makes operation even more efficient. SwissTEQ at its best.



Technical specifications	TC40+	TC80+	TC160	TC240	TC400
External dimensions (wxhxd) in mm	650x504x512	750x534x602	800x720x680	890x820x720	990x920x900
Internal dimensions (wxhxd) in mm	385x370x308	485x400x398	535x580x475	625x680x515	725x780x695
Internal volume (l)	40	80	160	240	400
Shelves (standard/max.)	2/5	2/5	2/8	2/8	2/10
Temp. range approx. >5 °C oRt to (°C)	275	275	275	275	275
Temp. variation at 50/150 °C (± °C)	0.6/1.2	0.6/1.5	0.8/1.8	0.8/2.1	1.0/2.5
Temp. fluctuation at 100 °C (± °C)	0.2	0.2	0.2	0.2	0.2
Heating-up time 70/150 °C (in min.)	8/20	10/25	12/30	16/30	20/40
SalvisTEQ controller	Yes	Yes	Yes	Yes	Yes
Display	Touch	Touch	Touch	Touch	Touch
Ports	USB, RJ45	USB, RJ45	USB, RJ45	USB, RJ45	USB, RJ45

Options

- Product temperature controller
- Program- and user package
- Process graph
- Redundant PT-100 probe
- Factory temperature mapping
- LAN-Interface
- Additional memory
- Additional USB or RJ45 port
- Entry port 20 mm
- Entry port 40 mm
- IQ/OQ draft paper, 3 hard copies
- Freely assignable analog outputs
- Programmable power socket
+ point calibration
- Potentialfree contact

Accessories

- Wire shelves (standard)
- Fresh air filter
- Product temperature probe
- Wall bracket